

12 DC

CYCLONE

1109 10th Street NE, East Grand Forks, MN 56721 Phone: (218)773-6602 Fax: (218)773-6607 1038 North Cedar Street, New Castle, PA 16102 Phone: (724)202-6740 Fax: (724)202-6794

Options

Electric Powered 40 HP 480 VAC 3 PH **Bi-powered** Filter Standard Qx Media 80/20 Blend SB (Spun Bonded Polyester) MERV 12 initial rating SBTX (HEPA Equivalent) **HEPA Secondary Final Filter** Filter Restriction Warning Light **Pulse System Onboard Air Compressor** Waste Removal **Gravity Dump Electric Powered Auger** Hydraulic Powered Auger Vibrator – Air Powered Vibrator – Electric Powered **Frame Configuration** Skid With Gravity Dump Skid With Auger Discharge Trailer With Auger Discharge Crane Pick Points Fork Lift Pockets Hitch 2 ^{5/16}" Ball coupler Pintle Lunette **Storage** Storage Boxes Jack Heavy Duty Jack Fuel Large Fuel Fill Grease Gun **Tie Down Points** Dryer Air Dryer Paint **Custom Company Color**

Standard Features

Filtration 18 top loading cartridges Filter Cleaning Timed cycle reverse air pulse Air Inlets Four 16" inlet ports, two each side Air to Cloth Ratio 2.56:1 at 12,000 cfm Filter Media 4,680 sq. ft. moisture resistant cellulose resin material (standard) Efficiency 99.8% at 0.5 micron particle after initial dust load MERV 12 initial rating Material Discharge Hydraulic powered auger Dimensions 117"H x 99"W x 252"L Engine Isuzu Diesel 4LE1 56hp Tier 4i Fan Non-Overloading, Spark Resisting Air Flow Rates 12,000 cfm @ 12" w.c. Fuel Consumption 2.6 Gallons per hour Fuel Storage 40 gallons Electrical System 12V dc Weight 8,000 lbs. actual Brakes Electric Paint ETI Gray Warranty One Year or 1500 hours Whichever occurs first limited

www.entechindustries.com