

EnTech Industries

1109 10th Street NE, East Grand Forks, MN 56721
Phone: (218)773-6602 Fax: (218)773-6607

1038 North Cedar Street, New Castle, PA 16102
Phone: (724)202-6740 Fax: (724)202-6794

40 DC CYCLONE



Standard Features

Filtration 60 top loading cartridges
Filter Cleaning Timed cycle reverse air pulse
Air Inlets Six 20" inlet ports, minimum two in use
Air to Cloth Ratio 2.56:1 at 40,000 cfm
Filter Media 15,600 sq. ft. moisture resistant cellulose resin material (standard)
Efficiency 99.8% at 0.5 micron particle after initial dust load
MERV 12 initial rating
Material Discharge Hydraulic powered auger
Dimensions 142"H x 96"W x 384"L
Engine John Deere 6068 = 6.8L
Fan Non-Overloading, Spark Resisting
Air Flow Rates 40,000 cfm @ 12" w.c.
Fuel Consumption 7.5 Gallon per hour
Fuel Storage 120 gallons
Electrical System 12V dc
Weight 20,000 lbs. actual
Brakes Electric
Paint ETI Gray

Warranty One Year or 1500 hours
Whichever occurs first limited

Options

Diesel Powered

Liquid Cooled Tier 3 158hp

Electric Powered

150 HP 480 VAC 3 PH

Filter

Standard Qx Media 80/20 Blend

SB (Spun Bonded Polyester) MERV 12 initial rating

SBTX (HEPA Equivalent)

HEPA Secondary Final Filter

Filter Restriction Warning Light

Pulse System

Onboard Air Compressor

Waste Removal

Gravity Dump

Electric Powered Auger

Hydraulic Powered Auger

Vibrator – Air Powered

Vibrator – Electric Powered

Frame Configuration

Skid With Gravity Dump

Skid With Auger Discharge

Trailer With Auger Discharge

Crane Pick Points

Fork Lift Pockets

Hopper Configuration

Quick release inlet connectors and clamps

Hitch

Pintle Lunette

Storage Storage Boxes

Jack Heavy Duty Jack

Fuel Large Fuel Fill

Grease Gun

Tie Down Points

Dryer Air Dryer

Paint Custom Company Color