

1109 10th Street NE, East Grand Forks, MN 56721 Phone: (218)773-6602 Fax: (218)773-6607 1038 North Cedar Street, New Castle, PA 16102 Phone: (724)202-6740 Fax: (724)202-6794

45 DC CYCLONE



Filtration 60 top loading cartridges

Filter Cleaning Timed cycle reverse air pulse

Air Inlets Six 20" inlet ports, minimum three in use

Air to Cloth Ratio 2.62:1 at 45,000 cfm

Filter Media 17,160 sq. ft. moisture resistant

cellulose resin material (standard)

 $\textbf{Efficiency} \ 99.8\% \ at \ 0.5 \ micron \ particle \ {\tt after \ initial \ dust \ load}$

MERV 12 initial rating

Grease Fittings Located within 2 banks centrally located

Lifting 4 lifting points and 2 Fork Pockets evenly balanced

Convenience All controls, banks and switches are

located on the "drivers" side of the machine

Material Discharge Hydraulic powered auger

Discharge Barrel Adapters Included

Dimensions 10'H x 8'5^{1/2}"W x 28'7^{1/8}"L

Motor 3 Phase x 480 VAC

Fan Non-Overloading, Spark Resisting

Directly drive off of the Motor

Air Flow Rates 45,000 cfm @ 14" w.c.

Electrical System 12V dc 3 Phase x 480 VAC for Main

and Hydraulic motors Transformed down to 120 volt for pulse system

Weight 25,000 lbs. actual

Paint ETI Gray

Warranty One Year or 1500 hours

Whichever occurs first limited

Options

Filter

Standard Qx Media 80/20 Blend

SB (Spun Bonded Polyester) MERV 12 initial rating

SBTX (HEPA Equivalent)

HEPA Secondary Final Filter

Filter Restriction Warning Light

Waste Removal

Gravity Dump

Electric Powered Auger

Hydraulic Powered Auger

Vibrator – Air Powered

Vibrator – Electric Powered

Frame Configuration

Skid With Gravity Dump

Skid With Auger Discharge

Crane Pick Points

Fork Lift Pockets

Hopper Configuration

Quick release inlet connectors and clamps

Storage Storage Boxes

Jack Heavy Duty Jack

Fuel Large Fuel Fill

Grease Gun

Tie Down Points

Dryer Air Dryer

Paint Custom Company Color