

EnTech Industries

1109 10th Street NE, East Grand Forks, MN 56721
Phone: (218)773-6602 Fax: (218)773-6607

6 DC CYCLONE ELECTRIC SKID



Standard Features

Filtration 9 top loading cartridges
Filter Cleaning Timed cycle reverse air pulse
Air Inlets Two 16" inlet ports, one per side
Air to Cloth Ratio 2.56:1 at 6,000 cfm
Filter Media 2,340 sq. ft. moisture resistant cellulose resin material (standard) QX Media
Fan Non-Overloading, Spark Resisting
Air Flow Rates 6,000 cfm @ 12" w.c.
Efficiency 99.8% at 0.5 micron particle after initial dust load
MERV 12 initial rating
Material Discharge
Telescopic drop legs to set dump height

Dimensions

115"H x 75"W x 123"L
In transport position

Motor

20 HP 480V 3 Phase

Mobility

Crane Pick Points
Fork Lift Pockets
Tie Down Points

Extras Grease Gun

Weight 4,000 lbs. actual

Paint ETI Gray

Warranty One Year or 1500 hours
Whichever occurs first limited

Options

Filters SB (Spun Bonded Polyester) MERV 12 initial rating
SBTX (HEPA Equivalent)
HEPA Secondary Final Filter
Discharge Optional vibrator